

Coatings and Process Development for Reduced Energy Automotive OEM Manufacturing

DE-EE0005777

PPG, Dürr Systems USA & North Dakota State University

January 1, 2015 – June 30, 2018

Caroline S. Harris, Ph.D., PPG

U.S. DOE Advanced Manufacturing Office Program Review Meeting
Washington, D.C.
July 19, 2018

This presentation does not contain any proprietary, confidential, or otherwise restricted information.

Overview

Timeline

- Start: 01/01/2015
- End: 06/30/2018
 - BP₃ completed

Budget

	Federal Budget	Cost Share	Total Budget
BP 1	963,561	389,161	1,352,722
BP 2	1,120,670	455,734	1,576,404
BP 3	888,118	428,827	1,316,945
Total	2,972,349	1,273,722	4,246,071

Total Cost: \$4,146,077

Barriers

- Technical Target
 - Low temperature coating system
 - Monoboath prototype
- Technical Barriers
 - Sustainable Manufacturing
 - Energy Reduction

Partner


- North Dakota State University
- DÜRR Systems USA, Inc.

Project Objective

- Develop coatings, processes and facility design to reduce energy consumption in automotive OEM paint shops


70% of the automotive assembly plant energy is consumed in the paint shop

Paint Shop Energy Consumption by Process



- Technical Barriers
 - Maintaining coating properties at lower temperature cure
 - Low temperature cross-link chemistries not commercial
 - Adoption of waterborne technologies and VOC restrictions
 - Process optimization compatibility with “Brownfield” conversion

Technical Innovation – Reduced Energy Process



- Lower Oven Temperature
- Reduction in Waste Heat
- Faster Time Between Layer Applications
- Lowers Fresh Air Demand in Oven
- Reduced Temperature/Humidity Control Requirements
- Enable Lightweighting– Temperature Sensitive Substrates


Technical Approach – Low Temperature Cure

Low Temperature Cure Coating

- Development of new low temperature cure polymers and formulas
 - Oven temperature reduction $140^{\circ}\text{C} \rightarrow \leq 100^{\circ}\text{C}$
 - Dehydration redesign for smaller footprint, lower energy
- Target layers include: Primer, Basecoat and Clearcoat
- North Dakota State University: High-throughput material analysis
- DüRR Systems Inc.: Application system modeling, design, and fabrication




Project
Focus



Technical Approach – Process Analysis

LEAPP™ Reference System Process



Compacts the process further

- Reduce Ambient Flash time from 5 min to 2 min
- Reduce Heated Flash time from 7 min to 90 sec
- Increase Heated Flash Temperature from 70°C to 100°C
- Reduce Cool down time from 2 min to 90 sec
- Reduce Final Bake Temperature from 145°C to 80°C
- Reduce oven time from 30-35 min to 25-28 min

36% Energy Reduction


(34,500 MWh)*

\$820,000/yr Op. Cost Savings

*\$4.1MM capital savings**

*For a two line plant,
with 60 jobs per hour

Results and Accomplishments



- ✓ Coating system developed in 3 colors: silver, white, and black
- ✓ Lab scale simulations completed using monoboath concept
 - ✓ Robotic paint application of low temperature cure topcoat systems demonstrated on a door skin



Transition

- PPG has a long history of automotive OEM innovations
 - Cationic electrodeposition, B1:B2™ Compact Process
 - LEAPP™ continues this tradition
- PPG Public Announcement Press Release
 - <http://www.ppgautocoatings.com/News/06-12-2018-PPG-to-introduce-low-energy-paint-pro>
- PPG Presentation at Inaugural SURCAR NA Congress
 - <http://northamerica.surcar-community.com/>



Questions?



We protect and beautify the world™

www.ppg.com