Biomass Feedstock National User Facility Capabilities for Plastic Processing and Recycling


Idaho National Laboratory

June 8, 2023




"Waste" at Material Recovery Facilities

- Post-consumer recycling is collected at facilities for material recovery and recycling efforts
- Even state-of-the-art equipment can miss or reject significant material that could be recycled due to contaminants or lack of a market
- Significant plastics and biogenic fiber wastes are being landfilled that could be utilized as resources




Material Recycling Facility Schematic



MRF Residuals

Emmet County Michigan

- Dual stream recycling facility
- #1 and #2 plastics and metals removed for recycling
- Office paper and corrugated cardboard removed for recycling



Fractionation – Pilot Scale Separations

Suitability of separations technologies to produce high-fidelity streams for a given end use



Air classifiers



Nanoranch sorter



Ballistic screening



Eddy current separator



AMPs robotic separation

Orbital screens

These unit operations may be used for both herbaceous, woody, and MSW separations, but often lend themselves more effectively to one or the other due to the different challenges and characteristics of each.

Not pictured: Disc screens, brush screens


IDAHO NATIONAL LABORATORY

Reconfigurable Fractional Milling Loop

- Multi-stage milling and separations to manage quality
 - Removal of soil
 - Capture of atspec fractions
 - Recycle to achieve a narrow size distribution
- Reconfiguration enables tailored fractionation for multiple feedstocks and conversion pathways



New Spectroscopic Analysis Tools will Improve Artificially Intelligent Robotic Separations




New tools, like Mid-IR, cameras will allow us to better characterize plastics in MSW for separations using artificial intelligencebased software.




BETO FY-20 Multi-Topic FOA - NanoRanch

- Multi-Sensor Suite
 - NIR multiple wave ranges
 - MIR
 - XRF
- Collect hyperspectral data of MSW stream
- Train AI to identify MSW components
- Demonstrate separation












BETO FY-20 Multi-Topic FOA – Amp Robotics







FY21 BETO Multi-Topic FOA – Amp Robotics

- Understand impact of MSW contamination on conversion
 - Use hyperspectral sensors to identify contaminants
 - Identify impact of contaminants on pyrolysis (Michigan Tech)
 - Train AI to select MSW with best properties for pyrolysis and remove other contaminated materials
 - Route materials to appropriate applications



Fundamental Deconstruction – Unique Capabilities









A 50mm screw extruder with temperature control >200°C is being used to compound biomass and plastics for 3D printing

Fundamental Deconstruction and Handling

BFNUF performs small-scale studies on deconstruction using specific tools to:

- Develop purer separation results.
- Better understand material handling challenges.
- Improve success of technology at a larger, industrial scale.

General Capabilities

Deconstruction Mechanisms

Mill	Impact	Attrition	Shear	Compression
Condux	Primary		Secondary	
Tornado	Primary			
Vibrating Ball		Secondary		Primary
Attrition		Primary	Secondary	
PolarFit				Primary
Disc Refiner			Primary	Secondary

Handling & Densification




Screw Extruder



Fluidized Bed Agglomerator

Gravity Screening









Recycling Challenges with Multilayered Packaging

Multilayer composite materials cannot currently be recycled because they are mixtures of various plastics and metals contaminated with pigments and dyes.



BFNUF capabilities aim to advance recycling methods for multilayered composite material.


BFNUF Process for Multilayer Package Recycling



Each capability upgrade plays a role in expanding research capabilities towards enabling new feedstocks for the coming decade.

Thermal preprocessing and mechanical reformatting

- Investigation of thermal treatment to remediate chlorine content in wastes
- Produce a more consistent solid fuel or solid feedstock
- Project with Convergen Energy and Michigan Technological University










Kolapkar, Shreyas S., et al. "Integrated torrefaction-extrusion system for solid fuel pellet production from mixed fiber-plastic wastes: Techno-economic analysis and life cycle assessment." *Fuel Processing Technology* 226 (2022): 107094.

Plastic Decontamination Studies

Detergent wash

Samples washed with detergent and water







Chemical wash

Samples washed with dimethyl ether (DME)





Rebecca M. Brown, Amber N. Hoover, Jordan L. Klinger, Bradley D. Wahlen, Damon Hartley, Hyeonseok Lee, Vicki S. Thompson.

Decontamination of Municipal Solid Waste Increases Low and High Temperature Conversion Yields


Submitted to Frontiers Energy Research

Rural Waste

RUMPKE

Source waste from rural community
Characterize the waste streams
Salyersville, KY pop. 1536 in Magoffin County, pop. 11,500






DARPA ReSource Program: Bringing MSW Processing Systems to the Battlefield

- The military needs deployable technology to convert battlefield waste into useful products
 - Petroleum, lubricants, oils, textiles, nutrients
 - Strict size, weight, and power limitations
- INL's role is to make clean, sorted, reactive feedstocks out of battlefield waste
 - Unit operations included in system
 - Crushing and perforating for increased bulk density and enhanced cleaning
 - DME cleaning of dirty plastic and paper
 - NIR identification for automated sorting
 - Delamination of layered plastics
 - Shredding materials to < 5mm
- INL is designing/building functional systems that will be deployed to teams at MIT, Michigan Tech, and Battelle Memorial Institute in September






INL's Deployable Waste Processing System: Δ-S



Crusher/Perforator and Shredder

- Collaboration with Forest Concepts
- > 20kg/day throughput
- 1.2m tall, 50 kg
- Output: 5mm particles and strips



NIR Material Identification System

- INL developed model and app
- Portable NIR spec and probe
- Model and app run on Raspberry Pi
- Adding new sensors for layered plastics



MSW Solvent Cleaning System

- DME solvent cleaning
- Integrating delamination process

IDAHO NATIONAL LABORATORY



Battelle Energy Alliance manages INL for the U.S. Department of Energy's Office of Nuclear Energy. INL is the nation's center for nuclear energy research and development, and also performs research in each of DOE's strategic goal areas: energy, national security, science and the environment.