

Full Scale Engine Demonstration of Additively Manufactured High Gamma Prime Turbine Blades

DE-LC-000L059
ORNL/Solar Turbines
10/1/18-9/30/19

Presenter: Ryan Dehoff, Ph.D.
PI: Michael Kirka, Ph.D.
Oak Ridge National Laboratory

U.S. DOE Advanced Manufacturing Office Program Review Meeting
Washington, D.C.
June 11th, 2019

This presentation does not contain any proprietary, confidential, or otherwise restricted information.

Overview

Barriers and Challenges:

- High Temperature Ni Superalloys are extremely crack prone during processing (considered non-weldable material)
- Certified critical rotating components have not been implemented in the hot section of a gas turbine

AMO MYPP Connection:

- Materials for harsh environments, combined heat and power, and additive manufacturing

Timeline:

Project Start Date: 10/01/2018
Budget Period End Date: 09/31/2019
Project End Date: 09/31/2019

Project Budget and Costs:

Budget	DOE Share	Cost Share	Total	Cost Share %
Overall Budget	\$1,500,000	\$3,800,000	\$5,300,000	71.6%
Approved Budget (BP-1&2)	\$1,500,000	\$3,800,000	\$5,300,000	71.6%
Costs as of 3/31/19	\$786,198	\$114,049	\$900,247	14.5%

Team



Michael Kirka-Project Lead

Yousub Lee-Process Modeling

Vincent Paquit-Data Analytics Lead

Derek Rose-In-situ Defect Detection

Amir Ziabari-CT Reconstruction



David Adair-Project Lead

Daniel Ryan-Materials & Processes

Drew Dominique-Machining & Fixtures

Brian Drouin-3D Optical Scans



William Halsey-Data Sciences




Paul Brackman-NDE Analysis



Daniel Herrington-Voxel innovations

Project Objectives

- Problem: Processing science and pathway for certification and qualification of defect prone materials critical rotating components fabricated through additive manufacturing do not exist
- Objective: Perform full-scale engine test using additive manufactured turbine blades to demonstrate similar or better performance to conventionally manufactured components
 - Approach: Utilize computational tools to certify a set of additively manufactured turbine blades to be hot-fired for an engine validation trial
 - Challenges:
 - Materials are traditionally non-weldable and defect prone
 - Certification and qualification tools do not exist for critical rotating AM components
 - Perceived notion AM material properties are inferior to cast material
- Project enables accelerated manufacturing of high performance components and systems for improving energy efficiency in gas turbine engines




Solar Turbines

A Caterpillar Company

Technical Innovation

Present: Investment Casting




Proposed: Electron Beam Melting



- Enabling novel airfoil designs through AM enhances engine performance and reduces fuel consumption
 - Every 1% efficiency gain saves \$2 million
- Impactful Outcomes:
 - Short Term: Enabled pathway for fabrication of novel prototype airfoil designs and decreased engine development cycles
 - Long Term: Digital framework for qualification and certification of critical AM components for commercial production with additional advancement of materials for extreme environments

Technical Approach:

- Cracking in AM Ni-Superalloys is scan pattern dependent
- Process Optimization performed on Mercury 50 Blade Geometry
- Determined efficient procedure for eliminating cracking based on in-situ monitoring, data analytics and modeling
- Demonstration of multiple build to fabricate a full set of blades






RESULT: Crack-free complex blade geometry

Technical Approach


- Determined methodology for final finishing, inspection, and qualification



Surface Finishing



X-ray Computed Tomography






In-situ data registration for statistical analysis

Results and Accomplishments

MS 1	Demonstrate ability to complete 10 builds and perform identical in-situ process monitoring to show no crack formations in the airfoil geometries using previously developed machine learning algorithms to analyze the in-situ data. ✓
MS 2	Confirmation of repeatable mechanical performance of the AM Inconel 738 as determined through destructive mechanical testing ✓
MS 3	Confirmation that a complete set of AM Inconel 738 airfoils through data analytics techniques are defect (crack) free to proceed with spin-pit testing
MS 4	Successful spin-pit test of rotor comprised of AM Inconel 738 airfoils as confirmed by Solar Turbines that no blade failed during room temperature testing
MS 5	Hot-fire of a Stage II rotor comprised entirely of AM fabricated Inconel 738 airfoils in a Mercury 50 engine

- Process parameters optimized for fabrication of defect-free airfoils
- Mechanical properties meet or exceed cast Inconel 738
 - Exhibit reliable repeatability
- Data analytics framework developed for identifying defective blades and creating a digital twin
- Manufacturing science for finishing blades successful with accuracy meeting or exceeding cast counterparts

Next steps:



Transition (beyond DOE assistance)

- Moonshot program accelerated development cycle of new materials for AM through digital and computational means
 - Program enabled a strategy of engagement with turbine companies on additive and end applications
 - Technology readiness level (TRL) of 6 will be demonstrated
- Successful demonstration of rapid prototyping new blade designs to enhance engine performance/efficiency
- Program enabled dissemination of Inconel 738 materials processing coupled with data analytics tools
- To be presented at ASME Turbo Expo 2019: Paper GT2019-90966
- Significant knowledge gained related to control processes, finishing processes, qualification and certification, high fidelity CT
 - Reassurance Ni-base superalloys fabricated via AM can be commercialized for critical applications
- GE, Siemens interested in Inconel 738 and other higher temperature Ni-base superalloys fabricated through EBM

